

PROPRIETARY AND CONFIDENTIAL	Description		NAME	DATE	PART#	REV	
THE INFORMATION CONTAINED IN THIS	3/16" Hose Barb, Valved,	DRAWN BY:	SCW	27-Oct-14	20ACV-SB3-03	1	
DRAWING IS THE SOLE PROPERTY OF INDUSTRIAL SPECIALTIES MFG. AND IS MED SPECIALITES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDUSTRIAL SPECIALTIES MFG. AND IS MED SPECIALITES IS PROHIBITED.	Panel Mount Hose Barb Thumb-Latch Type Socket Coupling, 1/8" Flow, Natural Acetal Body and Terminations, Stainless Steel Thumb-Latch, Springs and Pins, 1/2"-24UNS Nickel Plated Brass Panel Nut	SHEET 1 OF 3		OF 3			
		SCALE 2.5:1		2.5:1	Industrial Specialties Mfg. IS Med Specialties		
		DO	NOT SCALE	DRAWING	13 Wed Specialties		


Specifications

Body and Termination Material	Natural Acetal (POM) - FDA and NSF Compliant for Food Contact				
Seal Material Option	Buna-N O-ring - FDA and NSF Compliant for Food Contact				
Sedi Maleriai Opilori	O-rings lubricated with Dow Corning 200 food grade silicone oil.				
Internal Valve Material	Natural Acetal (POM) - FDA and NSF Compliant for Food Contact				
Internal Valve Spring Material	316 Stainless Steel				
Thumb-latch Material	301 Stainless Steel				
Thumb-latch Spring Material	304 Stainless Steel				
Pin Material	316 Stainless Steel				
Pin Spring Material	302 Stainless Steel				
Panel Mount Nut	1/2"-24UNS Electrodeposited Nickel Plated Brass				
Operating Pressure Range	Vacuum to 120 psi (8.3 bar)				
Operating Temperature Range	-40° F to 180° F (-40° C to 82° C)				
Flow Capacity	1/8" Size				
	It is the sole responsibility of the system designer and user to select				
	products suitable for their specific application requirements and				
	to ensure proper installation, operation, and maintenance of				
C	these products.				
Compatibility Statement	Material compatibility, product ratings and application details				
	should be considered in the selection. Improper selection or use of				
	products described herein can cause personal injury or product				
	damage.				

Panel Mount Dimensions			
	PANEL OPENING	MAX PANEL THICKNESS	MIN PANEL THICKNESS
SOCKETS	Per Drawing	0.5"	0.05"
PLUGS	0.5"	0.3"	0.05"

PANEL NUT HEX SIZE PANEL NUT THREAD
5/8" 1/2" - 24UNS

5





20ACV-SB3-01 SHEET 2 OF 3

1

Ø.500^{+.010}

3





20ACV-SB3-03 SHEET 3 OF 3

5 4 3 2