



ISO 9001:2008 Certified Companies

4091 S. Eliot St., Englewood, CO 80110-4396 • 303-781-8486 • Fax 303-761-7939

CPP Series Ball Check Valves Specification Sheet

All aluminum ball check valves are 6000 series aluminum for greatest strength and corrosion resistance. Brass check valves are half-hard yellow brass. The valves ball seat, ball and spring are 300 series stainless steel alloy for maximum corrosion and wear resistance. Valves are suitable for use with any fuel type.

All ball check valves are individually calibrated to support a 30 inch column of gasoline and meet the ABYC 2-1/2 minute fire resistance test as described in ABYC Fuel System Standard H-24.

Flow Rate -- GPH			
	1/4" NPT	3/8" NPT	1/2" NPT
-1.5 psi	30	50	75
-3.0 psi	55	70	105

Item #	Inlet	Outlet	Material
CPP-14-4M-AL	1/4" Male NPT	1/4" Hose Barb	Aluminum
CPP-516-4M-B	1/4" Male NPT	5/16" Hose Barb	Brass
CPPL-516-4M-B	1/4" Male NPT	5/16" Long Hose Barb	Brass
CPP-516-4M-AL	1/4" Male NPT	5/16" Hose Barb	Aluminum
CPPL-516-4M-AL	1/4" Male NPT	5/16" Long Hose Barb	Aluminum
CPP-38-4M-B	1/4" Male NPT	3/8" Hose Barb	Brass
CPPL-38-4M-B	1/4" Male NPT	3/8" Long Hose Barb	Brass
CPP-38-4M-AL	1/4" Male NPT	3/8" Hose Barb	Aluminum
CPPL-38-4M-AL	1/4" Male NPT	3/8" Long Hose Barb	Aluminum
CPPL-38-6M-B	3/8" Male NPT	3/8" Long Hose Barb	Brass
CPP-38-6M-AL	3/8" Male NPT	3/8" Hose Barb	Aluminum
CPPL-12-6M-B	3/8" Male NPT	1/2" Long Hose Barb	Brass
CPPL-12-6M-AL	3/8" Male NPT	1/2" Long Hose Barb	Aluminum
CPPL-58-6M-B	3/8" Male NPT	5/8" Long Hose Barb	Brass
CPPL-58-6M-AL	3/8" Male NPT	5/8" Long Hose Barb	Aluminum
CPPL-38-8M-AL	1/2" Male NPT	3/8" Long Hose Barb	Aluminum
CPPL-12-8M-B	1/2" Male NPT	1/2" Long Hose Barb	Brass
CPPL-12-8M-AL	1/2" Male NPT	1/2" Long Hose Barb	Aluminum