


NOTE:

- CONTAINS BUNA-N O-RING, ST. STL. 302 SPRING AND BALLS.  
ASSEMBLY IS SECURED WITH AN ADHESIVE / SEALANT THREAD LOCKER
- THRU FLOW UPON DISCONNECT

TOLERANCES: unless otherwise noted

.XX ±.010  
.XXX ±.005  
ANGLES ±3 DEG.

DIMENSIONS ARE IN INCHES

PROPRIETARY AND CONFIDENTIAL	Description		NAME	DATE	PART#	REV
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INDUSTRIAL SPECIALTIES MFG. AND IS MED SPECIALITES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDUSTRIAL SPECIALTIES MFG. AND IS MED SPECIALITES IS PROHIBITED.	<b>10-32 Male UNF Coupler, Nickel Plated Brass</b>	DRAWN BY:	M.E.	5/15/2018	<b>MQC-C1032M-NI</b>	1
SHEET 1 OF 1			 <b>Industrial Specialties Mfg.</b> <b>IS Med Specialties</b>			