



Body Material: 316 SST
O-ring Material: Viton
Spring Material: 302 SST
Operating Pressure: Vacuum to 200 psig (14 bar)
Cracking Pressure: .5 to 150 psig (.034 bar to 10.3 bar)
Cracking Pressure Tolerance: < 2 psig (.14 bar): +/- 10% , 2 to 150 psig (.14 - 10.3 bar): +/- 5%
Temperature Range: -70°F to +400°F (-56°C to +204°C)

Note: 1. Proper filtration is recommended to prevent damage to the o-ring or sealing surface
 2. Valve may be assembled with o-rings lubricated with Krytox grease

PROPRIETARY AND CONFIDENTIAL	Description	NAME	DATE	PART#	REV
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INDUSTRIAL SPECIALTIES MFG. AND IS MED SPECIALITES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDUSTRIAL SPECIALTIES MFG. AND IS MED SPECIALITES IS PROHIBITED.	1/4" Male NPT x 1/4" Female NPT Relief Valve, Viton Seals, 70 psi Cracking Pressure, 316 Stainless Steel	DRAWN BY: M.E.	7/30/2020	RVL-4MF-V-SS316-70	1
		SHEET 1 OF 1		 Industrial Specialties Mfg. IS Med Specialties	