



Temp. Range 0°F to 350°F

302 Stainless Steel Shield Disc protects against dirt, bugs and contaminants

Viton O-Ring

Solid Brass Plunger

302 Stainless Steel Pull Ring for Manual Relief

SECTION A-A

Teflon Tape (not shown)

302 Stainless Steel Guide

302 Stainless Steel Spring Preset to 30 psi

Solid Brass Body

The precision spring is double heat treated to eliminate temperature / time fatigue.

PROPRIETARY AND CONFIDENTIAL

### Description

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INDUSTRIAL SPECIALTIES MFG. AND IS MED SPECIALITES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDUSTRIAL SPECIALTIES MFG. AND IS MED SPECIALITES IS PROHIBITED.

1/4" Male NPT Relief Valve, Viton O-Ring, Stainless Steel Spring-Guide-Pull Ring, 30 psi Cracking Pressure, Brass Plunger and Body

DRAWN BY:

NAME

M.E.

DATE

2/20/2017

PART#

URV-4-30

REV

1

SHEET 1 OF 1

SCALE: 3:2

DO NOT SCALE DRAWING



**Industrial Specialties Mfg.**  
**IS Med Specialties**